MEMO



SUBJECT

Enhanced Evaporation Particulate Air Monitoring

DATE

July 24, 2017

LOCATION

Yerington Mine Site 1 Austin Circle Yerington, NV 89447

FROM

Travis Phelps

ТО

Jack Oman

WORK RELEASE NUMBER

WR309438

OUR REF PROJECT NUMBER

BPOE3901.9438

COPIES TO

Dante Rodriguez John Batchelder Patrick Keller

Overview

This memo is intended to provide a plan of action in order to meet United States Environmental Protection Agency- (USEPA-) requested requirements for air quality monitoring associated with the operation of an Enhanced Evaporation System (EVS) at the Yerington Mine Site in Yerington, Nevada (the site). The USEPA has requested that air monitoring be performed to ensurethat the proposed recently approved EVS does not impact air quality in adjacent areas. To address these requirements, Arcadis has produced an air monitoring plan to establish particulate monitoring stations ar ound the site that would help evaluate the potential presence of impacts from operation of the EVS. As the USEPA has concerns about air particulate leaving the site, this air particulate monitoring plan will replace the proposed desiccant moisture monitoring plan.

Monitoring Plan

ARC proposes to set up three particulate matter less than 10 mi crons in diameter (PM $_{10}$) dust monitoring stations around the northwest perimeter of the mine site and so uth of Evaporation Ponds B and C in conjunction with a meteorological station on top of the Vat Lea ch Tailings (VLT) Heap Leach Pad (HLP). Locations of the monitoring stations are identified on the atta ched Figure 1. The dust monitoring stations will record data every 15 minut es using dataloggers along with the meteorological station, which would record wind speed and direction as well as other weather information per the schedule outlined below. All data will be correlated to create a relationship between wind speed, direction, and air particulate density. If no statistically significant increase in PM $_{10}$ is detected during 1 week of operation, then monitoring will b e discontinued.

Schedule

ARC proposes to monitor particulates for 1 week, during site wok hours, before the EVS startup to establish a benchmark for background particulate levels associated with regional and local dust-generating conditions. After the EVS startup, monitoring will continue for another week during site work hours (not just during the period of operation of the EVS). The current enhance d evaporation plan includes running the system for 3 hours per day and will provide an appropriate moni toring window to assess changes in particulate suspension and movement from system operation. Following the monitoring period, all data will be analysed, and a summary report showing results will be provided to the USEPA.

